

SDI VIDEO 234 CONNECTIONS BLACK EDITION

- Video SDI connection with cable Q11-234N (0,76/3,4/6,0). Stranded Copper Wire 7/0.254mm, Black color BNC SDI 4K in black with gold contacts
- Flexible cable, with a resistant PVC jacket of Ø 6.00mm.
- Al Screen + Tinned Copper Braid 100% Coverage.
- Suitable for mobile applications and intensive work.

REFERENCES

Code	Length / Resolution	Presentation
EQ 234N/0005N	0,5 m HD 3G 6G 12G	Bag
EQ 234N/0010N	1 m HD 3G 6G 12G	Bag
EQ 234N/0020N	2 m HD 3G 6G 12G	Bag
EQ 234N/0030N	3 m HD 3G 6G 12G	Bag
EQ 234N/0050N	5 m HD 3G 6G 12G	Bag
EQ 234N/0070N	7 m HD 3G 6G 12G	Bag
EQ 234N/0100N	10 m HD 3G 6G 12G	Bag
EQ 234N/0150N	15 m HD 3G 6G 12G	Bag
EQ 234N/0200N	20 m HD 3G 6G 12G	Bag
EQ 234N/0250N	25 m HD 3G 6G 12G	Shrink-wrapped
EQ 234N/0300N	30 m HD 3G 6G 12G	Shrink-wrapped
EQ 234N/0400N	40 m HD 3G 6G 12G	Shrink-wrapped
EQ 234N/0500N	50 m HD 3G 6G	Shrink-wrapped
EQ 234N/0600N	60 m HD 3G 6G	Shrink-wrapped

DESCRIPTION

- Supported signals / Maximum length

HD-SDI 150 m	1080p 30fps (SMPTE 292M) 720p 60fps
3G-SDI / Full HD 80 m	1080p 60fps (SMPTE 424M)
6G-SDI / 4K-UHD 60 m	2160p 30fps (SMPTE 2081)
12G-SDI / 4K-UHD 40 m	2160p 60fps (SMPTE 2082)

- The stranded wire provides high flexibility to the connection.
- High signal propagation speed and low attenuation.
- High coverage shielding against external interference.
- Minimal connector insertion loss due to gold-plated contacts.
- Clear sleeves on both ends for labeling.
- Emelec VíasCom strap to facilitate storage.
- Assembly carried out by experienced personnel and individually tested, ensuring a correct performance.

