

# SDI VIDEO 3007 CONNECTIONS

- Video SDI connection with cable Q11-3007 (1.0/4.6/7.0). Single strand Copper Wire 1/1.00mm, Black color. BNC SDI 4K with gold contacts.
- Flexible cable, with a resistant PVC jacket of Ø 7.00mm.
- Al Screen + Tinned Copper Braid 100% Coverage.
- Suitable for mobile applications and intensive work.

## REFERENCES

Code	Length / Resolution	Packaging
EQ 3007N/0600	60 m HD 3G 6G 12G	Coiled
EQ 3007N/0700	70 m HD 3G 6G 12G*	Coiled
EQ 3007N/0800	80 m HD 3G 6G	Coiled
EQ 3007N/0900	90 m HD 3G 6G	Coiled
EQ 3007N/1000	100 m HD 3G 6G*	Coiled

\*The optimal performance of the cable in these resolutions for the indicated lengths may be altered by the equipment used or the medium in which it is located.



## DESCRIPTION

- Supported signals / Maximum length

HD-SDI 200 m	1080p 30fps (SMPTE 292M) 720p 60fps
3G-SDI / Full HD 150 m	1080p 60fps (SMPTE 424M)
6G-SDI / 4K-UHD 100 m	2160p 30fps (SMPTE 2081)
12G-SDI / 4K-UHD 70 m	2160p 60fps (SMPTE 2082)

- The single strand wire provides a high reliability in demanding environments.
- High signal propagation speed and low attenuation.
- High coverage double screen against external interferences.
- Minimal connector insertion loss due to gold-plated contacts.
- Clear sleeves on both ends for labeling.
- Assembly carried out by experienced personnel and individually tested, ensuring a correct performance.