

Patch Cords LAN CAT6A F/FTP and CAT7 SF/FTP



Product Features

- 28AWG section flexible **polished copper** conductors.
- Individual shielding in pairs, each pair is shielded with Al Tape.
- Double Global Shielding Al Tape + Copper Braid for Cat.7.
- Global Shielding in Al Tape for Cat.6A.
- HDPE insulation and FRLSZH halogen-free cover.
- Flame retardant IEC 60332-2-1 (vertical flame propagation test).
- Low smoke emission IEC 61034-2.
- Halogen free IEC 60754-1.
- Acidity determination of EC 60754-2 gases.

Products Description

- Cat.7 and Cat.6A LAN connections designed for digital data transmission in mobile applications.
- Capable of working with signals of up to 600 MHz frequency for Cat.7 and 500 MHz for Cat.6A.
- Excellent conductivity.
- Effective protection against electromagnetic interference thanks to its double shielding.
- Compatible with previous versions Cat.5E and Cat.6.
- Shielded RJ45 connectors with gold plated contacts.
- Pins assigned according to the T568B termination.
- Presented in plastic bags.

CAT6A F/FTP

Code	Length
6AEC30050HF	0,5 m
6AEC30100BHF*	1,0 m
6AEC30150HF	1,5 m
6AEC30200HF	2,0 m
6AEC30300HF	3,0 m
6AEC30500HF	5,0 m
6AEC30700HF	7,0 m
6AEC31000HF	10,0 m
6AEC31500HF	15,0 m
6AEC32000HF	20,0 m
6AEC32500HF	25,0 m
6AEC33000HF	30,0 m

CAT7 SF/FTP

Code	Length
7EC30050HF	0,5 m
7EC30100HF	1,0 m
7EC30150HF	1,5 m
7EC30200HF	2,0 m
7EC30300HF	3,0 m
7EC30500HF	5,0 m
7EC30700HF	7,0 m
7EC31000HF	10,0 m
7EC31500HF	15,0 m
7EC32000HF	20,0 m
7EC32500HF	25,0 m
7EC33000HF	30,0 m

* Color: Blanco