

# DATA CAT7 7018 S/FTP CABLE REEL



- Q16-7018 4x2x23AWG CAT7 S/FTP Data Cable mounted in Cable Reel. Unifilar Copper Conductors 1/0.58 mm, Black. RJ45 with 50µ gold pins.
- Flexible cable, with a resistant Ø 7.80 mm PVC jacket.
- Individual AL Tape Screen for each pair + Global Tinned Copper Braid Screen 100% Coverage.
- Ideal for mobile applications and intense work.

## REFERENCES

Code	Length	Connector	Cable Reel*
R-DATA-7018/E/050	50 m	E	EVR-285
R-DATA-7018/T/050		T	EVR-285
R-DATA-7018/R/050		R	EVR-285
R-DATA-7018/E/070	70 m	E	EVR-310
R-DATA-7018/T/070		T	EVR-310
R-DATA-7018/R/070		R	EVR-310
R-DATA-7018/E/090	90 m	E	EVR-310
R-DATA-7018/T/090		T	EVR-310
R-DATA-7018/R/090		R	EVR-310
R-DATA-7018/E/100	100 m	E	EVR-310
R-DATA-7018/T/100		T	EVR-310
R-DATA-7018/R/100		R	EVR-310
R-DATA-7018/E/120	120 m	E	EVR-380
R-DATA-7018/T/120		T	EVR-380
R-DATA-7018/R/120		R	EVR-380

\*The cable reel used may vary depending on stock.



## DESCRIPTION

- Connector types:
  - E** Body + RJ45 50µ
  - T** RJ45 50µ Toolless
  - R** RJ45 50µ
- Fixed end with 2m of cable (included in the length) or machined central plate with female base.
- Transparent sleeves on both ends for labeling.
- Assembly carried out by experienced personnel and individually tested, ensuring perfect operation.
- Resistant to prolonged use and easy to wind thanks to being mounted on a reel.
- Cable holder with soft, ergonomic handle for comfortable transport. Front part with cable guide and crank for a easy winding. Locking piece on the back.
- Possibility of using Neutrik® connectors
- Q16-7018 4x2x23AWG CAT7 S/FTP Data Cable mounted in Cable Reel. Unifilar Copper Conductors 1/0.58 mm, Black. RJ45 with 50µ gold pins.
- Flexible cable, with a resistant Ø 7.80 mm PVC cover.
- Individual AL Tape Screen for each pair + Global Tinned Copper Braid Screen 100% Coverage.
- Ideal for mobile applications and intense work.



### EMELEC ViasCom

C/ Sant Galderic, 23 Nave 3 · Polígono Industrial de Ponent  
08395 Sant Pol de Mar (Barcelona) España  
T 937 601 166 · T 937 601 177 · F 937 601 361 · info@emelec.es