



DIGITAL DMX3 2110 CABLE REEL



R-DMX3-2110 DMX CABLE REEL 3PINS

- Data Cable Q16-7000 4x2x26AWG CAT7 mounted on Cable Reel. Multi-strand Copper Conductors 7/0.16mm, Black color. RJ45 with 50µ gold pins.
- Very flexible cable, with a resistant PVC cover of Ø 6.50mm.
- Individual AL Tape Shield for each pair + Global Tinned Copper Braid Shield 100% Coverage.
- Ideal for mobile applications and intensive work.

REFERENCES

Night blue code	Black code	Cable length	Cable Reel*
R-DMX3-2110/030	R-DMX3-2110N/030	30 m	EVR-250
R-DMX3-2110/040	R-DMX3-2110N/040	40 m	EVR-250
R-DMX3-2110/050	R-DMX3-2110N/050	50 m	EVR-250
R-DMX3-2110/060	R-DMX3-2110N/060	60 m	EVR-250
R-DMX3-2110/070	R-DMX3-2110N/070	70 m	EVR-250
R-DMX3-2110/080	R-DMX3-2110N/080	80 m	EVR-250
R-DMX3-2110/090	R-DMX3-2110N/090	90 m	EVR-310
R-DMX3-2110/100	R-DMX3-2110N/100	100 m	EVR-310

*The cable reels used may vary according to stock.



EVR-250



EVR-310



XLR M 3p



XLR H 3p

DESCRIPTION

- Transmission of digital signals DMX-AES/EBU 110 Ohms.
- Flexible cable, with a resistant PVC cover of Ø 6.00mm. Ideal for mobile applications.
- 2m of cable (included in the length) on the front connected to the XLR Female.
- Transparent sleeves at both ends for labeling.
- Assembly carried out by experienced personnel and individually tested, ensuring perfect operation.
- Resistant to prolonged use and easy to wind thanks to being mounted on a reel.
- Cable Reel with soft and ergonomic handle for a comfortable transport. Front part with cable guide and crank for easy winding. Locking piece or wheel at the rear.
- Possibility of using Neutrik® connectors.

EMELEC ViasCom

C/ Sant Galderic, 23 Nave 3 · Polígono Industrial de Ponent
08395 Sant Pol de Mar (Barcelona) España
T 937 601 166 · T 937 601 177 · F 937 601 361 · info@emelec.es

www.emelec.es