



DIGITAL DMX5 702D CABLE REEL



- Multi-Pair Hose with two digital balanced cables Q3-702D 2x(2x0.22mm²) OFC mounted on Cable Reel. Very flexible, OFC Screen 100% Coverage with Ø 4.50mm PVC cover for each inner cable. Overall resistant PVC cover of Ø 11.00mm. Night Blue Color.
- 3-pin XLR Male and Female Emelec ViasCom® black color.
- Ideal for mobile applications.

REFERENCES

Black code	Cable length	Cable Reel*
R-DMX5-702D/020	20 m	EVR-310
R-DMX5-702D/030	30 m	EVR-310
R-DMX5-702D/040	40 m	EVR-310
R-DMX5-702D/050	50 m	EVR-310

*The cable reels used may vary according to stock.



EVR-310



XLR M 5p



XLR H 5p

DESCRIPTION

- Transmission of multiple DMX-AES/EBU 110 Ohms digital signals.
- Flexible multipair hose with a resistant PVC cover of Ø 11.00mm. Ideal for mobile applications.
- 2m of cable (included in the length) on the front connected to the XLR Female.
- 30cm stripping of the outer cover at both ends.
- Transparent sleeves at both ends for labeling.
- Assembly carried out by experienced personnel and individually tested, ensuring perfect operation.
- Resistant to prolonged use and easy to wind thanks to being mounted on a reel.
- Cable Reel with soft and ergonomic handle for a comfortable transport. Front part with cable guide and crank for easy winding. Locking wheel at the rear.
- Possibility of using Neutrik® connectors.

EMELEC ViasCom

C/ Sant Galderic, 23 Nave 3 · Polígono Industrial de Ponent
08395 Sant Pol de Mar (Barcelona) España
T 937 601 166 · T 937 601 177 · F 937 601 361 · info@emelec.es

www.emelec.es