



MICROPHONE 424 CABLE REEL



- Balanced Microphonic Cable Q3-424 2x0.22mm² OFC mounted on Cable Reel. Extra flexible, OFC Screen 100% Coverage with a resistant PVC cover of Ø 6.00mm. Color Black or possibility in other colors.
- 3-pin XLR Male and Female Emelec VíasCom® black color.
- Ideal for mobile applications.

REFERENCES

Black code	Cable length	Cable Reel*
R-MIC-424/030	30 m	EVR-250
R-MIC-424/040	40 m	EVR-250
R-MIC-424/050	50 m	EVR-250
R-MIC-424/060	60 m	EVR-250
R-MIC-424/070	70 m	EVR-250
R-MIC-424/080	80 m	EVR-250
R-MIC-424/090	90 m	EVR-310
R-MIC-424/100	100 m	EVR-310

*The cable reels used may vary according to stock.



DESCRIPTION

- Transmission of analog audio microphone signals.
- Flexible cable, with a resistant PVC cover of Ø 6.00mm. Ideal for mobile applications.
- 2m of cable (included in the length) on the front connected to the XLR Female.
- Transparent sleeves at both ends for labeling.
- Assembly carried out by experienced personnel and individually tested, ensuring perfect operation.
- Resistant to prolonged use and easy to wind thanks to being mounted on a reel.
- Cable Reel with soft and ergonomic handle for a comfortable transport. Front part with cable guide and crank for easy winding. Locking piece or wheel at the rear.
- Possibility of using Neutrik® connectors.

EMELEC VíasCom

C/ Sant Galderic, 23 Nave 3 · Polígono Industrial de Ponent
08395 Sant Pol de Mar (Barcelona) España
T 937 601 166 · T 937 601 177 · F 937 601 361 · info@emelec.es

www.emelec.es