



# MICROPHONE 502M CABLE REEL



- Multi-Pair Cable with two microphonic balanced cables Q3-502M 2x(2x0.20mm<sup>2</sup>) OFC mounted on Cable Reel. Very flexible, OFC TC Screen 100% Coverage with Ø 3.20mm PVC cover for each inner cable. Overall resistant PVC jacket of Ø 8.00mm. Color Black.
- 3-pin XLR Male and Female Emelec ViasCom® black color.
- Suitable for mobile applications.

## REFERENCES

Black code	Cable length	Cable Reel*
R-MIC-502M/020	20 m	EVR-310
R-MIC-502M/030	30 m	EVR-310
R-MIC-502M/040	40 m	EVR-310
R-MIC-502M/050	50 m	EVR-310
R-MIC-502M/060	60 m	EVR-310
R-MIC-502M/070	70 m	EVR-310
R-MIC-502M/080	80 m	EVR-310
R-MIC-502M/090	90 m	EVR-310
R-MIC-502M/100	100 m	EVR-310

\*The cable reels used may vary according to stock.



EVR-310



XLR M 3p



XLR H 3p

## DESCRIPTION

- Transmission of multiple analog audio microphone signals.
- Flexible multipair hose with a resistant PVC jacket of Ø 8.00mm. Suitable for mobile applications.
- 2m of cable (included in the length) on the front connected to the XLR Female.
- 30cm stripping of the outer jacket at both ends.
- Transparent sleeves at both ends for labeling.
- Assembly carried out by experienced personnel and individually tested, ensuring perfect operation.
- Resistant to prolonged use and easy to wind thanks to being mounted on a reel.
- Cable Reel with soft and ergonomic handle for a comfortable transport. Front part with cable guide and crank for easy winding. Locking wheel at the rear.
- Possibility of using Neutrik® connectors.

### EMELEC ViasCom

C/ Sant Galderic, 23 Nave 3 · Polígono Industrial de Ponent  
08395 Sant Pol de Mar (Barcelona) España  
T 937 601 166 · T 937 601 177 · F 937 601 361 · info@emelec.es

[www.emelec.es](http://www.emelec.es)