

SDI VIDEO 3006 CABLE REEL BLACK EDITION

- SDI Video Cable Q11-3006N (0.8/3.75/6.0) on Cable Reel. Single strand Copper Wire 1/0.80mm, Black color. BNC SDI 4K in black with gold contacts.
- Flexible cable, with a resistant PVC jacket of Ø 6.00 mm.
- Al Screen + Tinned Copper Braid 100% Coverage.
- Suitable for mobile applications and intense work.

REFERENCES

Code	Length / Resolution	Cable Reel*
R-SDI-3006N/020N	20 m HD 3G 6G 12G	EVR-250
R-SDI-3006N/030N	30 m HD 3G 6G 12G	EVR-250
R-SDI-3006N/040N	40 m HD 3G 6G 12G	EVR-250
R-SDI-3006N/050N	50 m HD 3G 6G 12G	EVR-250
R-SDI-3006N/060N	60 m HD 3G 6G	EVR-250
R-SDI-3006N/070N	70 m HD 3G 6G	EVR-250
R-SDI-3006N/080N	80 m HD 3G 6G	EVR-250

*The cable reels used may vary according to stock.

DESCRIPTION

- Supported signals / Maximum length

HD-SDI 160 m	1080p 30fps (SMPTE 292M) 720p 60fps
3G-SDI / Full HD 120 m	1080p 60fps (SMPTE 424M)
6G-SDI / 4K-UHD 85 m	2160p 30fps (SMPTE 2081)
12G-SDI / 4K-UHD 55 m	2160p 60fps (SMPTE 2082)

- The single strand wire provides a high reliability in demanding environments.
- High signal propagation speed and low attenuation.
- High coverage double screen against external interference.
- Minimal connector insertion losses thanks to gold-plated contacts.
- 2m of cable (included in the length) on the front.
- Clear sleeves on both ends for labeling.
- Resistant to prolonged use and easy winding thanks to being on a reel.
- Cable reel with soft and ergonomic handle for comfortable carrying. Front part with cable guide and crank for easy winding. Locking piece or wheel at the rear.
- Assembly carried out by experienced personnel and individually tested, ensuring a correct performance.



EMELEC VíasCom

C/ Sant Galderic, 23 Nave 3 · Polígono Industrial de Ponent
08395 Sant Pol de Mar (Barcelona) España
T 937 601 166 · T 937 601 177 · F 937 601 361 · info@emelec.es