

# SDI VIDEO 3007 CABLE REEL

- SDI Video Cable Q11-3007 (1.0/4.6/7.0) on Cable Reel. Single strand Copper Wire 1/1.00mm, Black color. BNC SDI with gold contacts.
- Flexible cable, with a resistant PVC jacket of Ø 7.00mm.
- Al Screen + Tinned Copper Braid 100% Coverage.
- Suitable for mobile applications and intense work.

## REFERENCES

Code	Length / Resolution	Cable Reel**
R-SDI-3007N/060	60 m <b>HD</b> <b>3G</b> <b>6G</b> <b>12G</b>	EVR-250
R-SDI-3007N/070	70 m <b>HD</b> <b>3G</b> <b>6G</b> <b>12G*</b>	EVR-250
R-SDI-3007N/080	80 m <b>HD</b> <b>3G</b> <b>6G</b>	EVR-310
R-SDI-3007N/090	90 m <b>HD</b> <b>3G</b> <b>6G</b>	EVR-310
R-SDI-3007N/100	100 m <b>HD</b> <b>3G</b> <b>6G*</b>	EVR-310

\*The optimal performance of the cable in these resolutions for the indicated lengths may be altered by the equipment used or the medium in which it is located.

\*\*The cable reels used may vary according to stock.



## DESCRIPTION

- Supported signals / Maximum length
 

<b>HD-SDI</b> 200 m	1080p 30fps (SMPTE 292M) 720p 60fps
<b>3G-SDI / Full HD</b> 150 m	1080p 60fps (SMPTE 424M)
<b>6G-SDI / 4K-UHD</b> 100 m	2160p 30fps (SMPTE 2081)
<b>12G-SDI / 4K-UHD</b> 70 m	2160p 60fps (SMPTE 2082)
- The single strand wire provides a high reliability in demanding environments.
- High signal propagation speed and low attenuation.
- High coverage double screen against external interferences.
- Minimal connector insertion losses thanks to the gold-plated contacts.
- 2m of cable (included in the length) on the front.
- Clear sleeves on both ends for labeling.
- Resistant to prolonged use and easy winding thanks to being on a reel.
- Cable reel with soft and ergonomic handle for comfortable carrying. Front part with cable guide and crank for easy winding. Locking piece or wheel at the rear.
- Assembly carried out by experienced personnel and individually tested, ensuring a correct performance.