

SDI VIDEO 3026 CONNECTIONS

- 2xSDI Video connection with Q11-3026 2x(0.8/3.75/6.0) cable. Unifilar Copper Conductor 1/0.80mm, Blue and Black color. BNC SDI 4K with gold contacts.
- Flexible internal cables with a resistant Ø6.00 mm PVC jacket. Global flexible outer jacket of Ø 13.50 mm PVC.
- AL Screen + Tinned Copper Braid 100% Coverage.
- Ideal for mobile applications and intense work.

REFERENCES

Code	Length / Resolution	Presentation
EQ3026/0005	0,5 m HD 3G 6G 12G	Bag
EQ3026/0010	1,0 m HD 3G 6G 12G	
EQ3026/0020	2,0 m HD 3G 6G 12G	
EQ3026/0030	3,0 m HD 3G 6G 12G	
EQ3026/0050	5,0 m HD 3G 6G 12G	
EQ3026/0070	7,0 m HD 3G 6G 12G	
EQ3026/0100	10,0 m HD 3G 6G 12G	
EQ3026/0150	15,0 m HD 3G 6G 12G	
EQ3026/0200	20,0 m HD 3G 6G 12G	
EQ3026/0250	25,0 m HD 3G 6G 12G	
EQ3026/0300	30,0 m HD 3G 6G 12G	
EQ3026/0400	40,0 m HD 3G 6G 12G	
EQ3026/0500	50,0 m HD 3G 6G 12G	
EQ3026/0600	60,0 m HD 3G 6G	
EQ3026/0700	70,0 m HD 3G 6G	
EQ3026/0800	80,0 m HD 3G 6G	

For BLACK BNC add 'N' at the end of the code.



DESCRIPTION

- Supported signals / Maximum length

HD-SDI 160 m	1080p 30fps (SMPTE 292M) 720p 60fps
3G-SDI / Full HD 120 m	1080p 60fps (SMPTE 424M)
6G-SDI / 4K-UHD 85 m	2160p 30fps (SMPTE 2081)
12G-SDI / 4K-UHD 55 m	2160p 60fps (SMPTE 2082)

- The single conductor of the cable provides the connection with a high reliability in highly demanding environments.
- High speed of signal propagation and low attenuation.
- High coverage double screen against external interference.
- Minimal connector insertion losses thanks to gold-plated contacts.
- 2m of cable (included in the length) on the front.
- Clear sleeves at both ends for labeling.
- Resistant to prolonged use and easy to wind thanks to being mounted on a reel.
- Cable holder with extendable handle for comfortable transport. Front part with cable guide and crank for easy winding. Piece or locking wheel at the rear.
- Assembly carried out by experienced personnel and individually tested, ensuring a correct performance.