

SDI VIDEO 3026 CABLE REEL

- Video Cable 2xSDI Q11-3026 2x(0.8/3.75/6.0) mounted on cable reel. Unifilar Copper Conductor 1/0.80mm, Blue and Black color. 4K SDI BNC with gold contacts used in lengths that allow 4K signals. 3G SDI BNC with gold pins used on all other lengths.
- Flexible internal cables with a resistant Ø 6.00mm PVC jacket. Global flexible outer PVC jacket of Ø 13.50 mm.
- AL Screen + Tinned Copper Braid 100% Coverage.
- Ideal for mobile applications and intense work.

REFERENCES

Code	Length / Resolution	Cable Reel**
R-SDI-3026/020	20,0 m HD 3G 6G 12G	EVR-285
R-SDI-3026/030	30,0 m HD 3G 6G 12G	EVR-310
R-SDI-3026/040	40,0 m HD 3G 6G 12G	EVR-380
R-SDI-3026/050	50,0 m HD 3G 6G 12G	
R-SDI-3026/060	60,0 m HD 3G 6G	EVR-490
R-SDI-3026/070	70,0 m HD 3G 6G	
R-SDI-3026/080	80,0 m HD 3G 6G	
R-SDI-3026/090	90,0 m HD 3G	
R-SDI-3026/100	100,0 m HD 3G	EVR-470
R-SDI-3026/110	110,0 m HD 3G	
R-SDI-3026/120	120,0 m HD 3G	
R-SDI-3026/130	130,0 m HD	
R-SDI-3026/140	140,0 m HD	
R-SDI-3026/150	150,0 m HD	
R-SDI-3026/160	160,0 m HD	

* For BLACK BNC add 'N' at the end of the code (Up to 80.0 m).

**The cable reels used may vary according to stock.



DESCRIPTION

- Supported signals/Maximum length

HD-SDI 160 m	1080p 30fps (SMPTE 292M) 720p 60fps
3G-SDI / Full HD 120 m	1080p 60fps (SMPTE 424M)
6G-SDI / 4K-UHD 85 m	2160p 30fps (SMPTE 2081)
12G-SDI / 4K-UHD 55 m	2160p 60fps (SMPTE 2082)

- The single conductor of the cable provides the connection with a high reliability in highly demanding environments.
- High speed of signal propagation and low attenuation.
- High coverage double screen against external interference.
- Minimal connector insertion losses thanks to gold-plated contacts.
- 2m of cable (included in the length) on the front.
- Clear sleeves at both ends for labeling.
- Resistant to prolonged use and easy to wind thanks to being mounted on a reel.
- Cable holder with extendable handle for comfortable transport. Front part with cable guide and crank for easy winding. Piece or locking wheel at the rear.
- Assembly carried out by experienced personnel and individually tested, ensuring a correct performance.