emelec® VíasCom

EQ6012 - LAN HOSES 2 x CAT.6 SF/UTP
2 x RJ45 / 2 x RJ45

NEW

Also mounted on our cable carriers

- Range of Connections made up of 2 LAN CAT.6 SF/UTP cables.
- Suitable for the transmission of two digital audio signals over Ethernet in the same cable.
- We use Q16-6012 cable, with a very flexible PVC jacket, ideal for mobile applications.
- They are offered in 3 versions according to the connectors used: RJ45 50 + Cap, RJ45 50 + Body, RJ45 50 Toolless.
- 30 cm of stripping of the outer cover at both ends.
- Transparent sleeves at both ends for labeling.
- Offered with Emelec VíasCom® connectors and with Neutrik® connectors.
- Recommended for fixed installations.
- References manufactured on demand.

E   T   R

CAT.6

BC	SHIELD
Bare Copper	Al Foil + TC Braid

RoHS

PVC FR	RJ45
Flame Retardant	50µ

Coding

EQ6012 / x / XXXX

Cable	LAN Connectors	Length					
Q16-6012	**E**: Body RJ45	**0010** 1,0 m		**0100** 10,0 m		**0500** 50,0 m	
		0020 2,0 m		**0150** 15,0 m		**0600** 60,0 m	
	R: RJ45	**0030** 3,0 m		**0200** 20,0 m		**0700** 70,0 m	
		0050 5,0 m		**0300** 30,0 m		**0800** 80,0 m	
	T: RJ45 Toolless	**0070** 7,0 m		**0400** 40,0 m		**0900** 90,0 m	

Composition

Cable Q16-6012 Emelec VíasCom®

2 x LAN CAT.6 SF/UTP

Conductors:	4x2x23AWG BC (1/0,53)
Shields:	Al Tape 100% coverage + TC braid global
Jacket:	PVC Flexible Ø 6,30 mm
Colour:	Black Numbered

Global Jacket: PVC Ø 17,00 mm

Emelec VíasCom® Connectors**

E   Body RJ45 + RJ45 50µ (EQ9310 + CL512)
T   RJ45 50µ Toolless (CL516)
R   RJ45 50µ (CL512) + Cap (CL110)

** Possibility of using Neutrik® connectors:
EtherCON® + RJ45 50µ (NE 8 MX-1 + CL512)

* Add "K" to the end of the code to indicate Neutrik® connectors:
EtherCON®+ RJ45 50µ (NE 8 MX-1 + CL512)

RJ45   RJ45

1 — 1 Orange-White
2 — 2 Orange
3 — 3 Green-White
4 — 4 Blue
5 — 5 Blue-White
6 — 6 Green
7 — 7 Brown-White
8 — 8 Brown

1 ... 8   1 ... 8