

EQ3126 - 2xSDI UNIFILAR VIDEO + POWER CONNECTIONS

Description

- Transmission of 2 digital video signals SDI 75 Ohms and Power.
- Flexible inner cables, with a resistant PVC sheath of Ø 6,00 mm.
- Power Supply of 3x2,5 mm² section with cover.
- Ideal for fixed and mobile applications.
- Transparent sleeves at both ends for labelling.
- BNC SDI 4K Male Emelec ViasCom® with gold contacts.

NEW



4K-UHD 3G-SDI

BC
Bare Copper

SHIELD
Al Foil + OFC TC Braid

GOLD
Gold Plated Contacts

RoHS



Coding

EQ3126/nn/XXXX					
Cable	Power	Length			
Q11-3126	02 Power Connector	0005	0,5 m	0200	20,0 m
		0010	1,0 m	0250	25,0 m
		0020	2,0 m	0300	30,0 m
	03 Schuko	0030	3,0 m	0400	40,0 m
		0050	5,0 m	0500	50,0 m
		0070	7,0 m	0600	60,0 m
	04 Power True	0100	10,0 m	0700	70,0 m
		0150	15,0 m	0800	80,0 m

Supported signals / Maximum length	
HD-SDI 160 m	1080p 30fps (SMPTE 292 m) 720P 60fps
3G-SDI / Full HD 120 m	1080p 60fps (SMPTE 424 m)
6G-SDI / 4K-UHD 85 m	2160p 30fps (SMPTE 2081)
12G-SDI / 4K-UHD 55 m	2160p 60fps (SMPTE 2082)

Composition

Emelec ViasCom® Cable Q11-3126
2x Video SDI 75Ω (0,80/3,75/6,00)
Conductors: 1/0,80 (20AWG) BC
Insulation: 3,75 mm FHDPE
Shields: Al Tape 100% Coverage
TC Braid global 90% Coverage
Jacket: PVC Flexible Ø 6,00 mm
Colour: Black and Blue
Power Supply
Conductors: 1x3x2,50 mm² BC
Jacket: PVC Flexible Ø 9,20 mm
Colour: Black
Global Jacket
Jacket: PVC Flexible Ø 18,50 mm
Colour: Black

Emelec ViasCom® Connectors*	
CC912 (BNC 75Ω 4K-UHD Male)	BNC VIDEO
CC812 (BNC 75Ω 3G-SDI Male)	
CC912/B (BNC 75Ω 4K-UHD Male Black)	
EQ9201 Power Connector IN	POWER 02
EQ9202 Power Connector OUT	
CP001 Schuko M	POWER 03
CP002 Schuko F	
EQ9281 Power True M	POWER 04
EQ9282 Power True F	