

EQ6030 - LAN HOSES CAT.6 SF/UTP + DMX + POWER SUPPLY 2,5 mm² RJ45 + XLR 3p/5p + Power Supply connectors

NEW

EQ6030/E3/02/XXXX



EQ6030/E3/03/XXXX



EQ6030/E3/04/XXXX



EQ6030/T3/02/XXXX



EQ6030/T3/03/XXXX



EQ6030/T3/04/XXXX



EQ6030/R3/02/XXXX



EQ6030/R3/03/XXXX



EQ6030/R3/04/XXXX

Description

- Range of Flexible Category 6 Hybrid Connection plus DMX plus Power Supply.
- CAT.6 SF/UTP LAN cable with 23AWG solid conductors, with Ø 6,30 mm PVC jacket.
- Digital signal DMX - AES/EBU 110Ω 2 x 0,25 mm²
- Power Supply of 2.5 mm² section with cover.
- Suitable for transmission of digital audio signals, DMX signals and power supply in the same cable.
- Flexible cables, with resistant PVC covers. Ideal for mobile applications.
- 1 m stripping of the outer cover at both ends.
- Transparent sleeves at both ends for labelling.
- Offered with Emelec ViasCom® connectors and with Neutrik® connectors.
- References manufactured on demand.



Coding

EQ6030/xn/nn/XXXX

Cable	LAN Connectors	XLR	Power	Length	
Q16-6030	E: Body RJ45	3 XLR 3 Pins	02 Power Connector	0010 1,0 m	0300 30,0 m
	R: RJ45	5 XLR 5 Pins	03 Schuko	0020 2,0 m	0400 40,0 m
				0030 3,0 m	0500 50,0 m
				0050 5,0 m	0600 60,0 m
	T: RJ45 Toolless		04 Power True	0070 7,0 m	0700 70,0 m
				0100 10,0 m	0800 80,0 m
				0150 15,0 m	0900 90,0 m
				0200 20,0 m	

Composition

Emelec ViasCom® Cable Q16-6030 LAN CAT.6 SF/UTP

Conductors: 4x2x23AWG BC (1/0,53)
 Shields: Al Tape 100% coverage + TC braid global
 Jacket: PVC Flexible Ø 6,30 mm
 Colour: Black

DMX 110Ω

Conductors: 1x2x0,25 mm² OFC 110 Ohms
 Shield: OFC Spiral 100% coverage
 Jacket: PVC Flexible Ø 6,00 mm
 Colour: Black

Power Supply

Conductors: 1x3x2,50 mm² BC
 Jacket: PVC Flexible Ø 10,00 mm
 Colour: Black

Global Jacket

Jacket: PVC Flexible Ø 22,50 mm
 Colour: Black

Emelec ViasCom® Connectors*

E	Body RJ45 + RJ45 50μ (EQ9310 + CL512)	LAN
T	RJ45 50μ Toolless (CL516)	
R	RJ45 50μ (CL512)	
EK9006/B	XLR F 3 pins Metallic Black	XLR 3
EK9001/B	XLR M 3 pins Metallic Black	
EK9008/B	XLR F 5 pins Metallic Black	XLR 5
EK9003/B	XLR M 5 pins Metallic Black	
EQ9201	Power Connector IN	POWER 02
EQ9202	Power Connector OUT	
CP001	Schuko M	POWER 03
CP002	Schuko F	
EQ9281	Power True M	POWER 04
EQ9282	Power True F	

* Possibility of using Neutrik® connectors: EtherCON® + RJ45 50μ (NE 8 MX-1 + CL512) and NC 3/5 MXX (XLR M 3/5P) + NC 3/5 FXX (XLR F 3/5P)
 * Add "K" to the end of the code to indicate Neutrik® connectors