

## EQ6032 - LAN HOSES 2x CAT.6 SF/UTP + 2xDMX + POWER SUPPLY 2,5 mm<sup>2</sup> RJ45 + XLR 3p/5p + Power Supply connectors

**NEW**

EQ6032/E3/02/XXXX



EQ6032/E3/03/XXXX



EQ6032/E3/04/XXXX



EQ6032/T3/02/XXXX



EQ6032/T3/03/XXXX



EQ6032/T3/04/XXXX



EQ6032/R3/02/XXXX



EQ6032/R3/03/XXXX



EQ6032/R3/04/XXXX

### Description

- Range of Flexible 2 x Category 6 Hybrid Connection plus 2 x DMX plus Power Supply.
- 2 x CAT.6 SF/UTP LAN cable with 23AWG solid conductors, with Ø 6,30 mm PVC jacket.
- 2 x Digital signals DMX - AES/EBU 110Ω 2 x 0,25 mm<sup>2</sup>
- Power Supply of 2.5 mm<sup>2</sup> section with cover.
- Suitable for transmission of digital audio signals, DMX signals and power supply in the same cable.
- Flexible cables, with resistant PVC covers. Ideal for mobile applications.
- 1 m stripping of the outer cover at both ends.
- Transparent sleeves at both ends for labelling.
- Offered with Emelec ViasCom® connectors and with Neutrik® connectors.
- References manufactured on demand.



### Coding

#### EQ6032/xn/nn/XXXX

| Cable    | LAN Connectors   | XLR          | Power              | Length      |             |
|----------|------------------|--------------|--------------------|-------------|-------------|
| Q16-6032 | E: Body RJ45     | 3 XLR 3 Pins | 02 Power Connector | 0010 1,0 m  | 0300 30,0 m |
|          | R: RJ45          | 5 XLR 5 Pins | 03 Schuko          | 0020 2,0 m  | 0400 40,0 m |
|          |                  |              |                    | 0030 3,0 m  | 0500 50,0 m |
|          |                  |              |                    | 0050 5,0 m  | 0600 60,0 m |
|          | T: RJ45 Toolless |              | 04 Power True      | 0070 7,0 m  | 0700 70,0 m |
|          |                  |              |                    | 0100 10,0 m | 0800 80,0 m |
|          |                  |              |                    | 0150 15,0 m | 0900 90,0 m |
|          |                  |              |                    | 0200 20,0 m |             |

### Composition

#### Emelec ViasCom® Cable Q16-6032 2 x LAN CAT.6 SF/UTP

Conductors: 4x2x23AWG BC (1/0,53)  
Shields: Al Tape 100% coverage + TC braid global  
Jacket: PVC Flexible Ø 6,30 mm  
Colour: Black Numbered

#### 2 x DMX 110Ω

Conductors: 1x2x0,25 mm<sup>2</sup> OFC 110 Ohms  
Shield: OFC Spiral 100% coverage  
Jacket: PVC Flexible Ø 6,00 mm  
Colour: Black Numbered

#### Power Supply

Conductors: 1x3x2,50 mm<sup>2</sup> BC  
Jacket: PVC Flexible Ø 10,00 mm  
Colour: Black

#### Global Jacket

Jacket: PVC Flexible Ø 24,00 mm  
Colour: Black

#### Emelec ViasCom® Connectors\*

|                                         |          |
|-----------------------------------------|----------|
| E Body RJ45 + RJ45 50µ (EQ9310 + CL512) | LAN      |
| T RJ45 50µ Toolless (CL516)             |          |
| R RJ45 50µ (CL512)                      |          |
| EK9006/B XLR F 3 pins Metallic Black    | XLR 3    |
| EK9001/B XLR M 3 pins Metallic Black    |          |
| EK9008/B XLR F 5 pins Metallic Black    | XLR 5    |
| EK9003/B XLR M 5 pins Metallic Black    |          |
| EQ9201 Power Connector IN               | POWER 02 |
| EQ9202 Power Connector OUT              |          |
| CP001 Schuko M                          | POWER 03 |
| CP002 Schuko F                          |          |
| EQ9281 Power True M                     | POWER 04 |
| EQ9282 Power True F                     |          |

\* Possibility of using Neutrik® connectors: EtherCON® + RJ45 50µ (NE 8 MX-1 + CL512) and NC 3/5 MXX (XLR M 3/5P) + NC 3/5 FXX (XLR F 3/5P)

\* Add "K" to the end of the code to indicate Neutrik® connectors