

R-DAT-6020 - LAN HOSES CAT.6 SF/UTP + POWER SUPPLY 2,5 mm² CABLE REEL

NEW**R-DAT-6020/E****R-DAT-6020/RC****Connectors****RJ45****POWER CONN****POWER TRUE****SCHUKO****Description**

- Range of Flexible one Category 6 Hybrid Connection plus Power Supply.
- CAT.6 SF/UTP LAN cable with 23AWG solid conductors, with Ø 6,30 mm PVC jacket.
- Power Supply of 2.5 mm² section with cover.
- Suitable for transmission of digital audio signals, DMX signals and power supply in the same cable.
- Flexible cables, with resistant PVC covers. Ideal for mobile applications.
- 1 m stripping of the outer cover at both ends.
- Transparent sleeves at both ends for labelling.
- Offered with Emelec ViasCom® connectors and with Neutrik® connectors.
- References manufactured on demand.

**Coding****R-DAT-6020/xC/nn/XXX**

Cable	LAN Connectors	Reel Ending	Power Connectors	Length	Reels
Q16-6020	E: Body RJ45 R: RJ45 T: RJ45 Toolless	C: With Chassis in the front panel None: Both ends in line	02: Power Connector 03: Schuko 04: Power True	030 30,0 m	EVR-380L
				040 40,0 m	
				050 50,0 m	
				060 60,0 m	
				070 70,0 m	EVR-470
				080 80,0 m	
				090 90,0 m	EVR-530

Composition**Emelec ViasCom® Cable Q16-6020 LAN CAT.6 SF/UTP**

Conductors: 4x2x23AWG BC (1/0,53)
 Shields: Al Tape 100% coverage + TC braid global
 Jacket: PVC Flexible Ø 6,30 mm
 Colour: Black
Power Supply
 Conductors: 1x3x2,50 mm² BC
 Jacket: PVC Flexible Ø 10,00 mm
 Colour: Black
Global Jacket
 Jacket: PVC Flexible Ø 21,50 mm
 Colour: Black

Emelec ViasCom® Connectors*

E Body RJ45 + RJ45 50µ (EQ9310 + CL512)
T RJ45 50µ Toolless (CL516)
R RJ45 50µ (CL512)
EC / TC / RC Chassis Body RJ45 CAT.6 (EQ9320)

EQ9201	Power Connector IN	POWER 2
EQ9202	Power Connector OUT	
EQ9262	Chassis Power Connector OUT	
CP001	Schuko M	POWER 3
CP002	Schuko F	
CP004	Chassis Schuko F	
EQ9281	Power True M	POWER 4
EQ9282	Power True F	
EQ9284	Chassis Power True F	

* Possibility of using Neutrik® connectors: EtherCON® + RJ45 50µ (NE 8 MX-1 + CL512) and NC 3/5 MXX (XLR M 3/5P) + NC 3/5 FXX (XLR F 3/5P)
 * Add "K" to the end of the code to indicate Neutrik® connectors