

R-DAT-6030 - LAN HOSES CAT.6 SF/UTP + DMX + POWER SUPPLY 2,5 mm² CABLE REEL

NEW**R-DAT-6030/E3****R-DAT-6030/RC5****Connectors****RJ45****XLR 3P****XLR 5P****POWER
CONN****POWER
TRUE****SCHUKO****Description**

- Range of Flexible Category 6 Hybrid Connection plus DMX plus Power Supply.
- CAT.6 SF/UTP LAN cable with 23AWG solid conductors, with Ø 6,30 mm PVC jacket.
- Digital signal DMX - AES/EBU 110Ω 2 x 0,25 mm²
- Power Supply of 2.5 mm² section with cover.
- Suitable for transmission of digital audio signals, DMX signals and power supply in the same cable.
- Flexible cables, with resistant PVC covers. Ideal for mobile applications.
- 1 m stripping of the outer cover at both ends.
- Transparent sleeves at both ends for labelling.
- Offered with Emelec ViasCom® connectors and with Neutrik® connectors.
- References manufactured on demand.

**Coding****R-DAT-6030/xCn/n/XXX**

Cable	LAN Connectors	Reel Ending	XLR	Power Connectors	Length	Reels
Q16-6030	E: Body RJ45 R: RJ45 T: RJ45 Toolless	C: With Chassis in the front panel None: Both ends in line	3: XLR 3 Pins 5: XLR 5 Pins	2: Power Connector 3: Schuko 4: Power True	030 30,0 m	EVR-380L
					040 40,0 m	
					050 50,0 m	
					060 60,0 m	
					070 70,0 m	EVR-530
					080 80,0 m	

Composition**Emelec ViasCom® Cable Q16-6030
LAN CAT.6 SF/UTP**

Conductors: 4x2x23AWG BC (1/0,53)
Shields: Al Tape 100% coverage + TC braid global
Jacket: PVC Flexible Ø 6,30 mm
Colour: Black

DMX 110Ω

Conductors: 1x2x0,25 mm² OFC 110 Ohms
Shield: OFC Spiral 100% coverage
Jacket: PVC Flexible Ø 6,00 mm
Colour: Black

Power Supply

Conductors: 1x3x2,50 mm² BC
Jacket: PVC Flexible Ø 10,00 mm
Colour: Black

Global Jacket

Jacket: PVC Flexible Ø 22,50 mm
Colour: Black

Emelec ViasCom® Connectors*

E Body RJ45 + RJ45 50μ (EQ9310 + CL512)
T RJ45 50μ Toolless (CL516)
R RJ45 50μ (CL512)
EC / TC / RC Chassis Body RJ45 CAT.6 (EQ9320)

EK9006/B XLR F 3 pins Metallic Black
EK9001/B XLR M 3 pins Metallic Black
EQ9162/B Chassis XLR M 3 pins Metallic Black
EK9008/B XLR F 5 pins Metallic Black
EK9003/B XLR M 5 pins Metallic Black
EQ9168/B Chassis XLR M 5 pins Metallic Black

EQ9201 Power Connector IN
EQ9202 Power Connector OUT
EQ9262 Chassis Power Connector OUT

CP001 Schuko M
CP002 Schuko F
CP004 Chassis Schuko F

EQ9281 Power True M
EQ9282 Power True F
EQ9284 Chassis Power True F

LAN

XLR 3

XLR 5

POWER 2

POWER 3

POWER 4

* Possibility of using Neutrik® connectors: EtherCON® + RJ45 50μ (NE 8 MX-1 + CL512) and NC 3/5 MXX (XLR M 3/5P) + NC 3/5 FXX (XLR F 3/5P)

* Add "K" to the end of the code to indicate Neutrik® connectors