

R-SDI-3126 - VIDEO HOSES 2xSDI UNIFILAR + POWER SUPPLY 2,5 mm² CABLE REEL



R-SDI-3126



R-SDI-3126/C

Connectors

BNC



POWER CONNEX



POWER TRUE



SCHUKO



Supported signals

Supported signals / Maximum length

HD-SDI 160 m	1080p 30fps (SMPTE 292 m) 720P 60fps
3G-SDI / Full HD 120 m	1080p 60fps (SMPTE 424 m)
6G-SDI / 4K-UHD 85 m	2160p 30fps (SMPTE 2081)
12G-SDI / 4K-UHD 55 m	2160p 60fps (SMPTE 2082)

Description

- Range of Flexible two Video SDI Hybrid Connection plus Power Supply.
- 2 x 20AWG SDI 75Ω Video cables, with Ø 6,00 mm PVC jacket.
- Power Supply of 2.5 mm² section with cover.
- Suitable for transmission of digital video signals up to 12G-SDI and power supply in the same cable.
- Flexible cables, with resistant PVC covers. Ideal for mobile applications.
- 1 m stripping of the outer cover at both ends.
- Transparent sleeves at both ends for labelling.
- Offered with Emelec ViasCom® connectors and with Neutrik® connectors.
- References manufactured on demand.



Coding

R-SDI-3126/C/nn/XXX

Cable	Reel Ending	Power Connectors	Length	Resolution	Reels
Q11-3126	C: With Chassis in the front panel None: Both ends in line	02 Power Connector 03 Schuko 04 Power True	020 20,0 m	HD 3G 6G 12G	EVR-380
			030 30,0 m	HD 3G 6G 12G	
			040 40,0 m	HD 3G 6G 12G	
			050 50,0 m	HD 3G 6G 12G	EVR-470
			060 60,0 m	HD 3G 6G	
			070 70,0 m	HD 3G 6G	
			080 80,0 m	HD 3G 6G	
			090 90,0 m	HD 3G	
			100 100,0 m	HD 3G	
			110 110,0 m	HD 3G	EVR-530
			120 120,0 m	HD 3G	

Composition

Emelec ViasCom® Cable Q11-3126

2 x SDI 75Ω (0,80/3,75/6,00)

Conductors: 1/0,80 (20AWG) OFC

Insulation: 3,75 mm FHDPE

Shields: Al Tape 100% Coverage
OFC TC Braid global
90% Coverage

Jacket: PVC Ø 6,00 mm
Colour: Black and Blue

Power Supply

Conductors: 1x3x2,50 mm² OFC
Jacket: PVC Flexible Ø 8,40 mm
Colour: Black

Global Jacket

Jacket: PVC Flexible Ø 18,50 mm
Colour: Black

Emelec ViasCom® Connectors*

CC912 (BNC 75Ω 4K-UHD Male)

CC812 (BNC 75Ω 3G-SDI Male)

CC912/B (BNC 75Ω 4K-UHD Male Black)

CC950/B (Chassis BNC 75Ω 4K-UHD Female Black)

EQ9201 Power Connector IN
EQ9202 Power Connector OUT
EQ9262 Chassis Power Connector OUT

CP001 Schuko M
CP002 Schuko F
CP004 Chassis Schuko F

EQ9281 Power True M
EQ9282 Power True F
EQ9284 Chassis Power True F

Emelec ViasCom® Reels*

EVR-380, EVR-380L, EVR-470 or EVR-530 depending on lengths

* The cable reels used may vary according to stock