

R-DAT-6014 – LAN HOSES 4x CAT.6 SF/UTP CABLE REEL

NEW



R-DAT-6014/E



R-DAT-6014/RC

RJ45



Coding

R-DAT-6014 / xC / XXX

Cable	LAN Connectors	Reel Ending	Length	Reels	
Q16-6014	E: Body RJ45	C: With Chassis in the front panel	030 30,0 m	EVR-380	
			040 40,0 m	EVR-380L	
	R: RJ45		050 50,0 m	EVR-470	
			060 60,0 m		
	T: RJ45 Toolless	None: Both ends in line	070 70,0 m		
			080 80,0 m		
			090 90,0 m		

Composition

Emelec ViasCom® Cable Q16-6014 4 x LAN CAT.6 SF/UTP

Conductors: 4x2x23AWG BC (1/0,53)
Shields: Al Tape 100% coverage
+ TC braid global
Jacket: PVC Flexible Ø 6,30 mm
Colour: Black Numbered

Global Jacket

Jacket: PVC Flexible Ø 19,00 mm
Colour: Black

Emelec ViasCom® Connectors*

E Body RJ45 + RJ45 50µ (EQ9310 + CL512)
T RJ45 50µ Toolless (CL516)
R RJ45 50µ (CL512)
EC / TC / RC Chassis Body RJ45 CAT.6 (EQ9320)

LAN

Description

- Range of Flexible 4 x Category 6 Connection.
- 4 x CAT.6 SF/UTP LAN cable with 23AWG solid conductors, with Ø 6,30 mm PVC jacket.
- Suitable for transmission of four digital audio/DMX signals in the same cable.
- Flexible cables, with resistant PVC covers. Ideal for mobile applications.
- 1 m stripping of the outer cover at both ends.
- Transparent sleeves at both ends for labelling.
- Offered with Emelec ViasCom® connectors and with Neutrik® connectors.
- References manufactured on demand.

* Possibility of using Neutrik® connectors: EtherCON® + RJ45 50µ (NE 8 MX-1 + CL512) and NC 3/5 MXX (XLR M 3/5P) + NC 3/5 FXX (XLR F 3/5P)

* Add "K" to the end of the code to indicate Neutrik® connectors